

S Sk F

Step-by-Step PDF Sewing Pattern and Instructions Designed to fit 12 - 13 inch Dolls such as Baby Alive®

> Skill level: Beginner

Copyright © 2023 Doll Tag Clothing



Sewing Pattern to fit 12 - 13 inch Baby Alive®



Copyright © 2023 Doll Tag Clothing

0

0

### Index

Page 1 - 2
Page 2
Page 3
Page 4 - 5
Page 6
Page 7

#### **Doll Model Size**

This pattern is designed to fit 12 to 13 inch Baby Alive® by Hasbro™ dolls.

### Fabric Guide

• Light weight and medium weight woven fabric

. . . . . . . . .

• Quilt cottons work well

#### You will need

- Fabric Remnant 5" x 17"
- Matching Thread
- 1/4" Wide Elastic 7"

### **Printing the Pattern**

- Pattern pieces are found at the end of the instructions. Check the scale of your pattern. Make sure your printer scale is set to "none".
- If you are using A4 Paper set and your scale is not correct set your printer to print "Letter" size.
- Simply cut out the pattern pieces or trace them onto pattern paper.

### **Cutting Instructions**

- Skirt Waistband Cut 1 on fold
- Skirt Flair Cut 1 on fold

onte	Elastic Casing Dimply a Skirt 12-13" Baby Alive kirt Waist Band - Cut 1 on fold	2 Layers
 •	Simply a Skirt	 †
center front	12-13" Baby Alive	
ont	Cut 1 on fold	Doll ta

### **Before You Begin**

- Seam allowance Sew a 1/4" seam unless otherwise stated.
- **"Finish off the seam"** This is to prevent fraying. If you do not have a serger, then use an overlock or zigzag stitch on your machine. Fray check can also be used. A nice zigzag to use on your machine: Set stitch length 2 and stitch width 2.
- "Finish off the seam" for 2 layers Trim the seam slightly and zigzag.


### **Skirt Instructions**

- 1. Finish the top long edge of the skirt waistband with a serger or zigzag stitch. Fold the edge over to the wrong side, 3/8", and press. Sew close to the edge creating the elastic casing.
- 2. Finish the bottom long edge of the skirt flair. Fold to the wrong side, 1/4", and press. Sew close to the edge creating the hem.
- Sew two rows of gather stitches at the top edge of the skirt flair.
  Row 1 - 1/8" from the edge
  Row 2 - 1/8" from the first row

# NOTE: A Gather stitch is a straight stitch with the longest stitch length setting on your machine.

 Pull the bottom thread of the gather stitches to gather the skirt flair.
Gather the flair to be the same length as the bottom of the waistband.

Tie the ends to keep the gathers in place. Even out the gathers.





Fold the seam allowance up towards the waistband.
Stitch 1/8" from the edge on the waistband side.
This topstitch will sew the seam allowance in place.

7. Cut a length of elastic, 7". Thread the elastic through the casing. Let it stick out slightly at the openings. Stitch the elastic down with a small zigzag stitch.


Repeat for the second end.

8. With right sides together, align the two short sides of the skirt. Sew and finish the seam allowance.

Turn the skirt right side out.

### Your skirt is complete!





## SUMMARY OF INSTRUCTIONS Simply a Skirt - 12 to 13 inch Baby Alive

- 1. Finish the top long edge of the skirt waistband with a serger or zigzag stitch. Fold the edge over to the wrong side, 3/8", and press. Sew close to the edge creating the elastic casing.
- 2. Finish the bottom long edge of the skirt flair. Fold to the wrong side, 1/4", and press. Sew close to the edge creating the hem.
- 3. Sew two rows of gather stitches at the top edge of the skirt flair.

Row 1 - 1/8" from the edge

Row 2 - 1/8" from the first row

NOTE: A Gather stitch is a straight stitch with the longest stitch length setting on your machine.

- Pull the bottom thread of the gather stitches to gather the skirt flair. Gather the flair to be the same length as the bottom of the waistband. Tie the ends to keep the gathers in place. Even out the gathers.
- 5. With right sides together, place the top of the skirt flair on the bottom of the waistband and align. Sew and finish the seam allowance.
- 6. Fold the seam allowance up towards the waistband. Stitch 1/8" from the edge on the waistband side. This topstitch will sew the seam allowance in place.
- 7. Cut a length of elastic, 7". Thread the elastic through the casing. Let it stick out slightly at the openings. Stitch the elastic down with a small zigzag stitch. *Repeat for the second end*.
- 8. With right sides together, align the two short sides of the skirt. Sew and finish the seam allowance.

Turn the skirt right side out.

#### Your skirt is complete!

### Over 200 patterns in my catalogue





### Welcome to my Doll World!



Dollplaysa.com South African Girl Doll

Dolltagclothing1@gmail.com

Pinterest.com/Liese\_Brouwer



Facebook.com/DollTagClothing

Instagram.com/dollplaysa/

Ravelry.com/designers/liese-brouwer

About file sharing - You have purchased 1 copy of this digital product from Doll Tag Clothing for your personal use. You do not have permission to copy, share or sell this pattern or parts thereof. You do not have permission to give it to someone else in any form. Selling or giving this pattern away or parts thereof violates our copyright and is wrong. Copyright © 2023 Doll Tag Clothing - All rights reserved

**Disclaimer** - These patterns are intended for personal use, not for large scale commercial purposes or manufacturing. When using this pattern to create an item for sale, it will be appreciated if you could give credit in your listing to Doll Tag Clothing.

Doll Tag Clothing is not affiliated with Baby Alive® or Hasbro™. No endorsement is implied.