



Simply a Skirt

Skill level:
Beginner

Step-by-Step PDF
Sewing Pattern and
Instructions
Designed to fit
13.5 inch Fashion
Dolls such as
My First Barbie™


Index

Cover Page	Page 1
Pattern Information	Page 2
Cutting Instructions	Page 2
Skirt Instructions	Page 3 - 4
Pattern Pieces	Page 5
Summary of Instructions	Page 6



Doll Model Size

This pattern is designed for 13.5 inch fashion doll such as My First Barbie™.
 Chest – 5-7/8” Waist – 4-5/8” Hips – 5-7/8”



Fabric Guide

- Light and medium weight woven fabric
- Quilters cotton works well

You Will Need


- Fabric remnant - 5” x 13”
- Matching Thread
- 1/4” wide Elastic – 5”

Printing the Pattern

- Pattern pieces are found at the end of the instructions.
- Check the scale of your pattern. Print files at 100%, “Scale None”, or “Actual Size”.
- If you are using A4 Paper set and your scale is not correct set your printer to print “Letter” size.
- Simply cut out the pattern pieces or trace them onto pattern paper.

Cutting Instructions

- Skirt Waist Band – Cut 1 on fold
- Skirt Flair – Cut 1 on fold



Before You Begin


- **Seam allowance** – Sew a 1/4” seam unless otherwise stated.
- **“Finish off the seam”** – This is to prevent fraying. If you do not have a serger, then use an overlock or zigzag stitch on your machine. Fray check can also be used. A nice zigzag to use on your machine: Set stitch length 2 and stitch width 2.
- **“Finish off the seam” for 2 layers** – *Trim* the seam slightly and zigzag.
- **Gather Stitch** – Straight stitch with the stitch length set to the highest setting of you machine. Normally 5.

Skirt Instructions

1. Finish the top long edge of the skirt waistband with a serger or zigzag stitch. Fold the edge over to the wrong side, 3/8”, and press. Sew close to the edge creating the elastic casing.
2. Finish the bottom long edge of the skirt flair. Fold to the wrong side, 1/4”, and press. Sew close to the edge creating the hem.
3. Sew two rows of gather stitches at the top edge of the skirt flair.
Row 1 – 1/8” from the edge
Row 2 – 1/8” from the first row
4. Pull the bottom thread of the gather stitches to gather the skirt flair.
Gather the flair to be the same length as the bottom of the waistband, 7.25”.
Tie the ends to keep the gathers in place. Even out the gathers.
5. With right sides together, place the top of the skirt flair on the bottom of the waistband and align. Sew and finish the seam allowance.



- Fold the seam allowance up towards the waistband. Stitch 1/8" from the edge on the waistband side. This topstitch will sew the seam allowance in place.



- Cut a length of elastic, 5". Thread the elastic through the casing. Let it stick out slightly at the openings. Stitch the elastic down with a small zigzag stitch.

Repeat for the second end.



- With right sides together, align the two short sides of the skirt. Sew and finish the seam allowance.





- Turn the skirt right side out.

The skirt is complete!



1 inch



Summary of Instructions

SIMPLY A SKIRT for 13.5 inch My First Barbie™

1. Finish the top long edge of the skirt waistband with a serger or zigzag stitch. Fold the edge over to the wrong side, 3/8", and press. Sew close to the edge creating the elastic casing.
2. Finish the bottom long edge of the skirt flair. Fold to the wrong side, 1/4", and press. Sew close to the edge creating the hem.
3. Sew two rows of gather stitches at the top edge of the skirt flair.
Row 1 – 1/8" from the edge
Row 2 – 1/8" from the first row
4. Pull the bottom thread of the gather stitches to gather the skirt flair.
Gather the flair to be the same length as the bottom of the waistband, 7.25".
Tie the ends to keep the gathers in place. Even out the gathers.
5. With right sides together, place the top of the skirt flair on the bottom of the waistband and align. Sew and finish the seam allowance.
6. Fold the seam allowance up towards the waistband. Stitch 1/8" from the edge on the waistband side. This topstitch will sew the seam allowance in place.
7. Cut a length of elastic, 5". Thread the elastic through the casing. Let it stick out slightly at the openings. Stitch the elastic down with a small zigzag stitch.
Repeat for the second end.
8. With right sides together, align the two short sides of the skirt. Sew and finish the seam allowance.
9. Turn the skirt right side out.

The skirt is complete!

Over 200 patterns in my catalogue!



with



www.dolltagclothing.com

Welcome to my Doll World!



Dollplaysa.com
South African Girl Doll



Facebook.com/DollTagClothing



Dolltagclothing1@gmail.com



Instagram.com/dollplaysa/



Pinterest.com/Liese_Brouwer



Ravelry.com/designers/liese-brouwer

About file sharing - You have purchased 1 copy of this digital product from Doll Tag Clothing for your personal use. You do not have permission to copy, share or sell this pattern or parts thereof. You do not have permission to give it to someone else in any form. Selling or giving this pattern away or parts thereof violates our copyright and is wrong. Copyright © 2023 Doll Tag Clothing - All rights reserved

Disclaimer - These patterns are intended for personal use, not for large scale commercial purposes or manufacturing. When using this pattern to create an item for sale, it will be appreciated if you could give credit in your listing to Doll Tag Clothing.

Doll Tag Clothing is not affiliated with Mattel®, My First Barbie™, Barbie™ or Ken™ Dolls. No endorsement is implied.